PROVISIONING - (Average Completion Notice Interval- Continued)

Data Retained Relating to CLEC Experience	Data Retained Relating to BST Experience
Report Month	BST Analog expected release 8/15/99 reports
CLEC Order Number	
Work Completion Date	
Work Completion Time	
Completion Notice Availability Date	
 Completion Notice Availability Time 	
Service Type	
Activity Type	
Geographic Scope	
NOTE: Code in parentheses is the corresponding	
header found in the raw data file.	
Retail Analog/Benchmark:	
Under Development at this time 8/15/99	

Revision date: 06/24/99 (taf)

PROVISIONING

Coordinated Customer Conversions

Definition:

This category measures the average time it takes BST to disconnect an unbundled loop from the BST switch and cross connect it to a CLEC's equipment. This measurement applies to service orders with and without INP, and where the CLEC has requested BST to provide a coordinated cutover.

Exclusions:

- Any order canceled by the CLEC will be excluded from this measurement.
- Delays due to CLEC following disconnection of the unbundled loop
- Unbundled Loops where there is no existing subscriber loop

Business Rules:

Where the service order includes INP, the interval includes the total time for the cutover including the translation time to place the line back in service on the ported line. The interval is calculated for the entire cutover time for the service order and then divided by items worked in that time to give the average per item interval for each service order.

Calculation:

• [(Completion Date and Time for Cross Connection of an Unbundled Loop)- (Disconnection Date and Time of an Unbundled Loop)] / Total Number of Unbundled Loop Items for the reporting period.

Report Structure:

- CLEC Specific
- CLEC Aggregate
- BST Aggregate

Level of Disaggregation:

- Reported in intervals <=5 minutes; >5,<15 minutes; >15 minutes, plus Overall Average interval
- Product Reporting Levels
 - > UNE Loops without INP
 - > UNE Loops with INP
- Geographic Scope
 - > State, Region, and further geographic disaggregation as required by State Commission Order

Data Retained Relating to CLEC Experience	Data Retained Relating to BST Experience
Report Month	No BST Analog Exists
CLEC Order Number	_
Committed Due Date (DD)	
 Service Type (CLASS_SVC_DESC) 	
Cutover Start Time	
Cutover Completion time	
 Portability start and completion times (INP Orders) 	
Total Items	
NOTE: Code in parentheses is the corresponding	
header found in the raw data file.	

Retail Analog/Benchmark:

There is no retail analog for this measurement because it measures cutting loops to the CLEC. Benchmark under development.

Revision date: 06/24/99 (taf)

PROVISIONING

Report/Measurement:

% Provisioning Troubles within 30 days of Service Order Activity

Definition:

Percent Provisioning Troubles within 30 days of Installation measures the quality and accuracy of installation activities.

Exclusions:

- Canceled Service Orders
- Order Activities of BST or the CLEC associated with internal or administrative use of local services (R Orders, Test Orders, etc.)
- D & F orders

Business Rules:

Measures the quality and accuracy of completed orders. The first trouble report from a service order after completion is counted in this measure. Subsequent trouble reports are measured in Repeat Report Rate. Reports are calculated searching in the prior report period for completed service orders and following 30 days after completion for a trouble report.

D & F orders are excluded as there is no subsequent activity following a disconnect.

Calculation:

% Provisioning Troubles within 30 days of Service Order Activity = \cdot (Trouble reports on all completed orders \cdot 30 days following service order(s) completion) / (All Service Orders in a completed in the report calendar month) X 100

Report Structure:

- CLEC Specific
- CLEC Aggregate
- BST Aggregate

Level of Disaggregation:

- Reported in categories of <10 line/circuits; > 10 line/circuits
- Dispatch / No Dispatch
- Product Reporting Levels
 - POTS Residence
 - POTS Business
 - DESIGN
 - ➤ PBX
 - CENTREX
 - ISDN
 - UNE 2 Wire Loop with INP (Design and Non-Design)
 - ➤ UNE 2 Wire Loop without INP (Design and Non-Design)
 - UNE Loop Other with INP (Design and Non-Design)
 - UNE Loop Other without INP (Design and Non-Design)
 - UNE Other (Design and Non-Design)
 - Switching (Under development)
 - Local Transport (Under development)
 - Combos (Under development)
 - > NP (Under development as separate category)
 - Local Interconnection Trunks
- Geographic Scope

Appendix D2 - SQM Reg 8-10-99

> State, Region, and further geographic disaggregation (MSA) as required by State Commission Order

PROVISIONING - (% Provisioning Troubles within 30 days of Service Order Activity - Continued)

Data Retained Relating to CLEC Experience	Data Retained Relating to BST Experience	
Report Month	Report Month	
CLEC Order Number and PON	BST Order Number	
 Order Submission Date(TICKET_ID) 	Order Submission Date	
Order Submission Time (TICKET_ID)	Order Submission Time	
Status Type	Status Type	
Status Notice Date	Status Notice Date	
Standard Order Activity	Standard Order Activity	
Geographic Scope	Geographic Scope	
NOTE: Code in parentheses is the corresponding		
header found in the raw data file.		
Retail Analog/Benchmark:		
CLEC Residence Resale / BST Residence Retail		
CLEC Business Resale / BST Business Retail		
CLEC Design / BST Design		
CLEC PBX, CENTREX, ISDN/ BST PBX, CENTREX, ISDN		
Interconnection Trunks-CLEC / Interconnection Trunks -BST		
UNEs-Retail Analog (Under Development at this time)		

Revision date: 06/24/99 (taf)

PROVISIONING

Report/Measurement:

Total Service Order Cycle Time (TSOCT) (under development 3Q99)

Definition:

This is a new measurement under development to measure the total service order cycle time from receipt of a valid service order request to the completion of the service order.

Exclusions:

- Canceled Service Orders
- Order Activities of BST or the CLEC associated with internal or administrative use of local services
- (Record Orders, Test Orders, etc.)
- D (Disconnect) and F (From) orders. (From is disconnect side of a move order when the customer moves to a new address).
- "L" Appointment coded orders (where the customer has requested a later than offered interval)

Business Rules:

The interval is determined for each order processed during the reporting period. This measurement combines two reports: FOC (Firm Order Confirmation) with Average Order Completion Interval. This interval starts with the receipt of a valid service order request and stops when the technician or system completes the order in SOCS. Elapsed time for each order is accumulated for each reporting dimension. The accumulated time for each reporting dimension is then divided by the associated total number of orders completed

Calculation:

Total Service Order Cycle Time (under development)

Report Structure:

- CLEC Specific
- CLEC Aggregate
- BST Aggregate

Level of Disaggregation:

- ISDN Orders included in Non Design GA Only
- Dispatch/No Dispatch categories applicable to all levels except trunks.
- Intervals under development
- Product Reporting Levels
 - Interconnection Trunks
 - POTS Residence
 - POTS Business
 - > DESIGN
 - > PBX
 - CENTREX
 - > ISDN
 - UNE 2 Wire Loop with INP (Design and Non-Design)
 - ➤ UNE 2 Wire Loop without INP (Design and Non-Design)
 - ➤ UNE Loop Other with INP (Design and Non-Design)
 - UNE Loop Other without INP (Design and Non-Design)
 - UNE Other (Design and Non-Design)
 - Switching (Under development)
 - Local Transport (Under development)
 - Combos (Under development)
 - NP (Under development as separate category)
 - Local Interconnection Trunks
- Geographic Scope

Appendix D2 - SQM Reg 8-10-99

> State, Region and further geographic disaggregation as required by State Commission Order

PROVISIONING - (Total Service Order Cycle Time (TSOCT) - Continued

Data Retained Relating to CLEC Experience	Data Retained Relating to BST Experience
 Report Month Interval for FOC CLEC Company Name Order Number (PON) Submission Date & Time (TICKET_ID) Completion Date (CMPLTN_DT) Service Type (CLASS_SVC_DESC) Geographic Scope 	 Report Month CLEC Order Number Order Submission Date & Time Order Completion Date & Time -Service Type Geographic Scope
NOTE: Code in parentheses is the corresponding header found in the raw data file.	
Retail Analog/Benchmark	
Under development (BST retail analog available	at this time would be Average Completion Interval)

Revision date: 06/24/99 (taf)

MAINTENANCE & REPAIR

Report/Measurement:

Missed Repair Appointments

Definition:

The percent of trouble reports not cleared by the committed date and time.

Exclusions:

- Trouble tickets canceled at the CLEC request.
- BST trouble reports associated with internal or administrative service.
- Customer Provided Equipment (CPE) troubles or CLEC Equipment Trouble.

Business Rules:

The negotiated commitment date and time is established when the repair report is received. The cleared time is the date and time that BST personnel clear the trouble and closes the trouble report in his Computer Access Terminal (CAT) or workstation. If this is after the Commitment time, the report is flagged as a "Missed Commitment" or a missed repair appointment. When the data for this measure is collected for BST and a CLEC, it can be used to compare the percentage of the time repair appointments are missed due to BST reasons. Note: Appointment intervals vary with force availability in the POTS environment. Specials and Trunk intervals are standard interval appointments of no greater than 24 hours.

Calculation:

Percentage of Missed Repair Appointments = Σ (Count of Customer Troubles Not Cleared by the Quoted Commitment Date and Time) / Σ (Total Trouble reports closed in Reporting Period) X 100

Report Structure:

- CLEC Specific
- CLEC Aggregate
- BST Aggregate

Level of Disaggregation:

ISDN Troubles included in Non-Design - GA ONLY

- Product Reporting Levels
 - POTS Residence, Business
 - Design
 - PBX, CENTREX and ISDN
 - UNE 2 Wire Loop (Design and Non Design)
 - > UNE Loop Other (Design and Non Design)
 - UNE Other (Design and Non Design)
 - Switching, Local Transport and Combos (under development)
 - Local Interconnection Trunks
- Dispatch/No Dispatch categories applicable to all product levels
- Geographic Scope
 - State, Region and further geographic disaggregation as required by State Commission Order (e.g. Metropolitan Service Area MSA)

Appendix D2 - SQM Reg 8-10-99

Data Retained Relating to CLEC Experience	Data Retained Relating to BST Experience
Report Month	Report Month
CLEC Company Name	BST Company Code
Submission Date & Time (TICKET_ID)	Submission Date & Time
Completion Date (CMPLTN_DT)	Completion Date
Service Type (CLASS_SVC_DESC)	Service Type
Disposition and Cause (CAUSE_CD &	Disposition and Cause (Non-Design /
CAUSE_DESC)	Non-Special Only)
Geographic Scope	Trouble Code (Design and Trunking Services)
	Geographic Scope
NOTE: Code in parentheses is the corresponding	
header found in the raw data file.	

MAINTENANCE & REPAIR - (Missed Repair Appointments - Continued)

Retail Analog/Benchmark

- CLEC Residence-Resale / BST Residence-Retail
- CLEC Business-Resale / BST Business-Retail
- CLEC Design-Resale / BST Design-Retail
- CLEC PBX, Centrex, and ISDN Resale/ BST PBX, Centrex, and ISDN Retail
- CLEC Trunking-Resale / BST Trunking-Retail
- UNEs Retail Analog (under development at this time.)

MAINTENANCE & REPAIR

Report/Measurement:

Customer Trouble Report Rate

Definition:

Initial and repeated customer direct or referred troubles reported within a calendar month per 100 lines/circuits in service.

Exclusions:

- Trouble tickets canceled at the CLEC request.
- BST trouble reports associated with administrative service.
- Customer provided Equipment (CPE) troubles or CLEC equipment troubles.

Business Rules:

Customer Trouble Report Rate is computed by accumulating the number of maintenance initial and repeated trouble reports during the reporting period. The resulting number of trouble reports are divided by the total "number of service" lines, ports or combination of existing for the CLEC's and BST respectively at the end of the report month.

Calculation:

Customer Trouble Report Rate = (Count of Initial and Repeated Trouble Reports in the Current Period) / (Number of Service Access Lines in service at End of the Report Period) X 100

Report Structure:

- CLEC Specific
- CLEC Aggregate
- BST Aggregate.

Level of Disaggregation:

ISDN Troubles included in Non Design - GA Only

- Product Reporting Levels
 - POTS Residence and Business
 - Design
 - PBX, CENTREX, and ISDN
 - UNE 2 Wire Loop (Design and Non Design)
 - UNE Loop Other (Design and Non Design)
 - UNE Other (Design and Non Design)
 - Switching , Local Transport, and Combos (under development)
 - > Local Interconnection Trunks
- Dispatch/No Dispatch categories applicable to all product levels
- Geographic Scope
 - State, Region and further geographic disaggregation as required by State Commission Order (e.g. Metropolitan Service Area MSA)

Data Retained Relating to CLEC Experience	Data Retained Relating to BST Experience
Report Month	Report Month
CLEC Company Name	BST Company Code
 Ticket Submission Date & Time (TICKET_ID) 	Ticket Submission Date & Time
 Ticket Completion Date (CMPLTN_DT) 	Ticket Completion Date
 Service Type (CLASS_SVC_DESC) 	Service Type
 Disposition and Cause (CAUSE_CD & 	Disposition and Cause (Non-Design /
CAUSE_DESC)	Non-Special Only)
 # Service Access Lines in Service at the end of period 	Trouble Code (Design and Trunking
Geographic Scope	Services)
NOTE: Code in parentheses is the corresponding header found in the raw data file.	 # Service Access Lines in Service at the end of period Geographic Scope

MAINTENANCE & REPAIR - (Customer Trouble Report Rate - Continued)

Retail Analog/Benchmark:

- CLEC Residence-Resale / BST Residence -Retail
- CLEC Business-Resale / BST Business-Retail
- CLEC Design-Resale / BST Design-Retail
- CLEC PBX, Centrex and ISDN Resale/ BST PBX, Centrex, and ISDN Retail
- CLEC Trunking-Resale / BST Trunking-Retail
- UNEs Retail Analog (under development at this time)

MAINTENANCE & REPAIR

Report/Measurement:

Maintenance Average Duration

Definition:

The Average duration of Customer Trouble Reports from the receipt of the Customer Trouble Report to the time the trouble report is cleared.

Exclusions:

- Trouble reports canceled at the CLEC request
- BST trouble reports associated with administrative service
- Customer Provided Equipment (CPE) troubles or CLEC Equipment Troubles.
- Trouble reports greater than 10 days

Business Rules:

For Average Duration the clock starts on the date and time of the receipt of a correct repair request. The clock stops on the date and time the service is restored (when the technician completes the trouble ticket on his/her CAT or work system).

Calculation:

Maintenance Average Duration = Σ (Date and Time of Service Restoration) – (Date and Time Trouble Ticket was Opened) / Σ (Total Closed Troubles in the reporting period)

Report Structure:

- CLEC Specific
- BST Aggregate
- CLEC Aggregate

Level of Disaggregation:

ISDN Troubles included in Non Design - GA Only

- Product Reporting Levels
 - POTS- Residence and Business
 - Design
 - PBX, CENTREX, and ISDN
 - UNE 2 Wire Loop (Design Non Design)
 - UNE Loop Other (Design Non Design)
 - UNE Other (Design Non Design)
 - Switching, Local Transport and Combos (under development)
 - Local Interconnection Trunks
- Dispatch/No Dispatch categories applicable to all product levels
- Geographic Scope
 - State, Region and further geographic disaggregation as required by State Commission Order (e.g. Metropolitan Service Area – MSA)

MAINTENANCE & REPAIR - (Maintenance Average Duration - Continued)

Data Retained Relating to CLEC Experience	Data Retained Relating to BST Experience	
Report Month	Report Month	
Total Tickets (LINE_NBR)	Total Tickets	
CLEC Company Name	BST Company Code	
Ticket Submission Date & Time (TIME_ID)	Ticket Submission Date	
Ticket Completion Date (CMPLTN_DT)	Ticket submission Time	
Service Type (CLASS_SVC_DESC)	Ticket completion Date	
Disposition and Cause (CAUSE_CD &	Ticket Completion Time	
CAUSE_DESC)	Total Duration Time	
Geographic Scope	Service Type	
NOTE: Code in parentheses is the corresponding header found in the raw data file.	 Disposition and Cause (Non – Design / Non-Special Only) Trouble Code (Design and Trunking Services) Geographic Scope 	
Retail Analog/Benchmark:		
CLEC Residence-Resale / BST Residence-Resale		
CLEC Business-Resale / BST Business-Retail		
CLEC Design-Resale / BST Design-Retail		
CLEC PBX, Centrex and ISDN Resale / BST PBX, Centrex and ISDN Retail		
CLEC Trunking-Resale /BST Trunking-Retail		
UNEs - Retail Analog (under development at this time)		

MAINTENANCE & REPAIR

Report/Measurement:

Percent Repeat Troubles within 30 Days

Definition:

Trouble reports on the same line/circuit as a previous trouble report received within 30 calendar days as a percent of total troubles reported.

Exclusions:

- Trouble Reports canceled at the CLEC request
- BST Trouble Reports associated with administrative service
- Customer Provided Equipment (CPE) Troubles or CLEC Equipment Troubles.

Business Rules:

Includes Customer trouble reports received within 30 days of an original Customer trouble report.

Calculation:

Percentage of Missed Repair Appointments = (Count of Customer Troubles where more than one trouble report was logged for the same service line within a continuous 30 days) / (Total Trouble Reports Closed in Reporting Period) X 100

Report Structure:

- CLEC Specific
- CLEC Aggregate
- BST Aggregate

Level of Disaggregation:

ISDN Troubles included in Non Design - GA Only

- Product Reporting Levels
 - POTS Residence and Business
 - Design
 - PBX, CENTREX and ISDN
 - UNE 2 Wire Loop (Design and Non Design)
 - > UNE Loop Other (Design and Non Design)
 - UNE Other (Design Non Design)
 - Switching, Local Transport and Combos (under development)
 - Local Interconnection Trunks
- Dispatch/No Dispatch categories applicable to all product levels
- Geographic Scope
 - State, Region and further geographic disaggregation as required by State Commission Order (e.g. Metropolitan Service Area - MSA)

Data Retained Relating to CLEC Experience	Data Retained Relating to BST Experience
Report Month	Report Month
 Total Tickets (LINE_NBR) 	Total Tickets
 CLEC Company Name 	BST Company Code
 Ticket Submission Date & Time 	Ticket Submission Date
(TICKET_ID)	Ticket Submission Time
 Ticket Completion Date (CMPLTN_DT) 	Ticket Completion Date
 Total and Percent Repeat Trouble Reports 	Ticket Completion Time
within 30 Days (TOT_REPEAT)	Total and Percent Repeat Trouble Reports
Service Type	within 30 Days
 Disposition and Cause (CAUSE_CD & 	Service Type
CAUSE_DESC)	Disposition and Cause (Non – Design/
 Geographic Scope 	Non-Special only)
	Trouble Code (Design and
NOTE: Code parentheses is the corresponding	Trunking Services)
header format found in the raw data file.	Geographic Scope

MAINTENANCE & REPAIR - (Percent Repeat Troubles within 30 Days - Continued)

Retail Analog/Benchmark:

- CLEC Residence-Resale / BST Residence-Retail
- CLEC Business- Resale / BST Business-Retail
- CLEC Design-Resale / BST Design-Retail
- CLEC PBX, Centrex and ISDN Resale / BST PBX, Centrex and ISDN Retail
- CLEC Trunking-Resale / BST Trunking-Retail
- UNEs Retail Analog (under development at this time)

MANTENANCE & REPAIR

Report/Measurement:

Out of Service (OOS) > 24 Hours

Definition:

For Out of Service Troubles (no dial tone, cannot be called or cannot call out) the percentage of troubles cleared in excess of 24 hours. (All design services are considered to be out of service.)

Exclusions:

- Trouble Reports canceled at the CLEC request
- BST Trouble Reports associated with administrative service
- Customer Provided Equipment (CPE) Troubles or CLEC Equipment Troubles.

Business Rules:

Customer Trouble reports that are out of service and cleared in excess of 24 hours. The clock begins when the trouble report is created in LMOS and the trouble is counted if the time exceeds 24 hours.

Calculation:

Out of Service (OOS) > 24 hours = (Total Troubles OOS > 24 Hours) / Total OOS Troubles in Reporting Period) X 100

Report Structure:

- CLEC Specific
- BST Aggregate
- CLEC Aggregate.

Level of Disaggregation:

ISDN Troubles included in Non Design - GA Only

- Product Reporting Levels
 - POTS Residence and Business
 - Design
 - PBX and CENTREX and ISDN
 - ➤ UNE 2 Wire Loop (Design and Non Design)
 - UNE Loop Other (Design and Non Design)
 - UNE Other (Design and Non Design)
 - Switching, Local Transport and Combos (under development)
 - Local Interconnection Trunks
- Dispatch/No Dispatch categories applicable to all product levels
- Geographic Scope
 - State, Region and further geographic disaggregation as required by State Commission Order (e.g. Metropolitan Service Area MSA)

Data Retained Relating to CLEC Experience	Data Retained Relating to BST Experience
Report Month	Report Month
Total Tickets	Total Tickets
CLEC Company Name	BST Company Code
Ticket Submission Date & Time	Ticket Submission Date
(TICKET_ID)	Ticket Submission time
 Ticket Completion Date (CMPLTN_DT 	Ticket Completion Date
Percentage of Customer Troubles out of	Ticket Completion Time
Service > 24 Hours (OOS>24_FLAG)	Percent of Customer Troubles out of
Service type (CLASS_SVC_DESC)	Service > 24 Hours
Disposition and Cause (CAUSE_CD &	Service type
CAUSE-DESC)	Disposition and Cause (Non – Design/
Geographic Scope	Non-Special only)
	Trouble Code (Design and
NOTE: Code in parentheses is the corresponding	Trunking Services)
header found in the raw data file.	Geographic Scope

Page 56 of 8911

Version 08/10/99 Georgia OSS Evaluation Master Plan Version 32.0

Appendix D2 - SQM Reg 8-10-99

MANTENANCE & REPAIR - (Out of Service (OOS) > 24 Hours - Continued)

Retail Analog/Benchmark:

- CLEC Residence-Resale / BST Residence- Retail
- CLEC Business-Resale / BST Business-Retail
- CLEC Design-Resale / BST Design-Retail
- CLEC PBX, Centrex and ISDN Resale / BST PBX, Centrex and ISDN Retail
- CLEC Trunking-Resale /BST Trunking- Retail
- UNEs Retail Analog (under development at this time.)

MAINTENANCE & REPAIR

Report/Measurement:	
OSS Interface Availability	
Definition:	
The percentage of time the OSS Interface is fund Availability percentage for the CLEC and BST in by them are captured.	ctionally available compared to scheduled availability. interface systems and for the legacy systems accessed
Exclusions:	
None	
Business Rules:	
This measure is designed to compare the OSS av	vailability versus scheduled availability of BST's legacy
systems.	
Calculation:	
OSS Interface Availability = (Actual System Fur	nctional Availability) / (Actual planned System
Availability) X 100	
Report Structure:	
CLEC Aggregate	
BST Aggregate	
BST/CLEC	
Level of Disaggregation:	
Region	
Data Retained Relating to CLEC Experience	Data Retained Relating to BST Experience
Availability of CLEC TAFI	Availability of BST TAFI
Availability of LMOS HOST, MARCH	Availability of LMOS HOST, MARCH
and SOCS	and SOCS
 CRIS, PREDICTOR, LNP, and OSPCM 	
(under development at this time)	
Retail Analog/Benchmark:	
Parity by design; Retail Analog	

MAINTENANCE & REPAIR

ixebui biyicasui emem.	Re	port	Meas	urement:
------------------------	----	------	------	----------

OSS Response Interval and Percentages

Definition:

The response intervals are determined by subtracting the time a request is received on the BST side of the interface until the response is received from the legacy system. Percentages of requests falling into each interval category are reported, along with the actual number of requests falling into those categories.

Exclusions:

Queries received during scheduled system maintenance time.

Business Rules:

This measure is designed to monitor the time required for the CLEC and BST interface system to obtain from BST's legacy systems the information required to handle maintenance and repair functions. The clock starts on the date and time when the request is received and the clock stops when the response has been transmitted through that same point to the requester.

Calculation:

OSS Response Interval = (Query Response Date and Time for Category "X") - (Query Request Date and Time for Category "X") / (Number of Queries Submitted in the Reporting Period) where, "X" is 0-4, ≥ 4 to 10, ≥ 10 , ≥ 30 seconds.

Report Structure:

- CLEC
- BST Residence
- BST Business (BST Total is under development at this time) by interface for each legacy system and function as appropriate.

Level of Disaggregation:

Region

Data Retained Relating to CLEC Experience	Data Retained Relating to BST Experience
CLEC Transaction Intervals	BST Business and Residence transaction
	Intervals

Retail Analog/Benchmark:

Retail Analog

Audit Verification

MAINTENANCE & REPAIR

Report/Measurement:	
Average Answer Time – Repair Centers	
Definition:	
This measure demonstrates an average response ti representative. The average time a CLEC Rep is answer.	me for the CLEC representative to contact a BST in queue waiting for the LCSC or UNE Center Rep to
Exclusions:	
None	
Business Rules:	
This measure is designed to measure the time required choice to the time of being answered. The clock significant queue for the next repair attendant and the clock significant. Level of Disaggregation: Region. CLEC/BST Service Centers and BST Residue.	starts when the CLEC Rep makes a choice to be put in tops when the repair attendant answers the call.
Calculation:	H-
Average Answer Time for BST's Repair Centers of entry into queue until ACD Selection) / (Total	= (Time BST Repair Attendant Answers Call) – (Time I number of calls by reporting period)
Report Structure:	
CLEC AggregateBST/CLEC Aggregate	
Data Retained Relating to CLEC Experience	Data Retained Relating to BST Experience
CLEC Average Answer Time	BST Average Answer Time
Retail Analog/Benchmark:	
Retail Analog Audit Verification	

Revision date: 06/09/99 (see)

Appendix D2 - SQM Reg 8-10-99

BILLING

Report/Measurement: Invoice Accuracy	
Definition:	
This measure provides the percentage of accuracy of the billing invoices rendered to CLECs during the	
current month.	
Exclusions:	
 Adjustments not related to billing errors (e.g., credits for service outage, special promotion credits, adjustments to satisfy the customer) 	
Business Rules:	
The accuracy of billing invoices delivered by BST to the CLEC must enable them to provide a degree of billing accuracy comparative to BST bills rendered to retail customers BST. CLECs request adjustments on bills determined to be incorrect. The BellSouth Billing verification process includes manually analyzing a sample of local bills from each bill period. The bill verification process draws from a mix of different customer billing options and types of service. An end-to-end auditing process is performed for new products and services. Internal measurements and controls are maintained on all billing processes.	
Calculation:	
Invoice Accuracy = (Total Billed Revenues during current month) – (Billing Related Adjustments during	
current month) / Total Billed Revenues during current month X 100	
Report Structure:	
CLEC Specific, CLEC Aggregate and BST Aggregate	
Level of Disaggregation :	
Product / Invoice Type	
Resale	
> UNE	
> Interconnection	
Geographic Scope	
> Region	
Data Retained Relating to CLEC Experience: Data Retained Relating to BST Performance:	
Report Month Report Month	
Invoice Type Retail Type	
Total Billed Revenue CRIS	
Billing Related Adjustments CABS To a Date of the Capacitan Control of the Capacitan C	
Total Billed Revenue	
Billing Related Adjustments	
Retail Analog/Benchmark	
Retail Analog	

Revision date: 08/02/99 (lg)

Appendix D2 - SQM Reg 8-10-99

BILLING

Report/Measurement:	
Mean Time to Deliver Invoices	
Definition:	
This measure provides the mean interval for billing	ng invoices
Exclusions:	
Any invoices rejected due to formatting or conten	t errors.
Business Rules:	
Measures the mean interval for timeliness of billing	
format. CRIS-based invoices are measured in bus	siness days, and CABS-based invoices in calendar
days.	
Calculation:	
Mean Time To Deliver Invoices = Σ [(Invoice Trans	
Cycle)] / (Count of Invoices Transmitted in Reporting	g Period)
Report Structure:	
CLEC Specific, CLEC Aggregate and BST Aggregat	e
Level of Disaggregation:	
Product / Invoice Type	
> Resale	
> UNE	
Interconnection	
 Geographic Scope 	
> Region	
Data Retained Relating to CLEC Experience:	Data Retained Relating to BST Performance:
 Report Month 	Report Month
 Invoice Type 	Retail Type
 Invoice Transmission Count 	> CRIS
 Date of Scheduled Bill Close 	> CABS
	Invoice Transmission Count
	Date of Scheduled Bill Close
Retail Analog/Benchmark:	
CRIS-based invoices will be released for delivery wit	
CABS-based invoices will be released for delivery w	ithin eight (8) calendar days.

Revision date: 07/30/99 (lg)

BILLING

Usage Data Delivery Accuracy Definition: This measurement captures the percentage of recorded usage that is delivered error free and in an acceptable format to the appropriate Competitive Local Exchange Carrier (CLEC). These percentages will provide the necessary data for use as a comparative measurement for BellSouth performance. This measurement captures Data Delivery Accuracy rather than the accuracy of the individual usage recording. Exclusions: None Business Rules: The accuracy of the data delivery of usage records delivered by BST to the CLEC must enable them to provide a degree of accuracy comparative to BST bills rendered to their retail customers. If errors are detected in the delivery process, they are investigated, evaluated and documented. Errors are corrected and the data retransmitted to the CLEC. Calculations: Usage Data Delivery Accuracy = ∑ [(Total number of usage data packs sent during current month) − (Total number of usage data packs requiring retransmission during current month)] / (Total number of usage data packs sent during current month) X 100 Report Structure: CLEC Specific, CLEC Aggregate and BST Aggregate Level of Disaggregation: Geographic Scope Region Pata Retained Relating to CLEC Experience: Report Month Record Type BellSouth Recorded Non BellSouth Recorded Non BellSouth Recorded Retail Analog/Benchmark: Retail Analog	Report/Measurement:	
This measurement captures the percentage of recorded usage that is delivered error free and in an acceptable format to the appropriate Competitive Local Exchange Carrier (CLEC). These percentages will provide the necessary data for use as a comparative measurement for BellSouth performance. This measurement captures Data Delivery Accuracy rather than the accuracy of the individual usage recording. Exclusions: None Business Rules: The accuracy of the data delivery of usage records delivered by BST to the CLEC must enable them to provide a degree of accuracy comparative to BST bills rendered to their retail customers. If errors are detected in the delivery process, they are investigated, evaluated and documented. Errors are corrected and the data retransmitted to the CLEC. Calculations: Usage Data Delivery Accuracy = \(\Sigma \) [(Total number of usage data packs sent during current month) - (Total number of usage data packs sent during current month) \(\Total number of usage data packs sent during current month) \(\Total number of usage data packs sent during current month) \(\Total number of usage data packs sent during current month) \(\Total number of usage data packs sent during current month) \(\Total number of usage data packs sent during current month) \(\Total number of usage data packs sent during current month) \(\Total number of usage data packs sent during current month) \(\Total number of usage data packs sent during current month) \(\Total number of usage data packs sent during current month) \(\Total number of usage data packs sent during current month) \(\Total number of usage data packs sent during current month) \(\Total number of usage data packs sent during current month) \(\Total number of usage data packs sent during current month) \(\Total number of usage data packs sent during current month) \(\Total number of usage data packs sent during current month) \(\Total number of usage data packs sent during current month) \(\Total number of usage data packs sent during cu	Usage Data Delivery Accuracy	
acceptable format to the appropriate Competitive Local Exchange Carrier (CLEC). These percentages will provide the necessary data for use as a comparative measurement for BellSouth performance. This measurement captures Data Delivery Accuracy rather than the accuracy of the individual usage recording. Exclusions: None Business Rules: The accuracy of the data delivery of usage records delivered by BST to the CLEC must enable them to provide a degree of accuracy comparative to BST bills rendered to their retail customers. If errors are detected in the delivery process, they are investigated, evaluated and documented. Errors are corrected and the data retransmitted to the CLEC. Calculations: Usage Data Delivery Accuracy = Σ [(Total number of usage data packs sent during current month) - (Total number of usage data packs requiring retransmission during current month)] / (Total number of usage data packs sent during current month) X 100 Report Structure: CLEC Specific, CLEC Aggregate and BST Aggregate Level of Disaggregation: Geographic Scope Region Pata Retained Relating to CLEC Experience: Report Month Record Type BellSouth Recorded Non BellSouth Recorded Non BellSouth Recorded Retail Analog/Benchmark:	Definition:	
measurement captures Data Delivery Accuracy rather than the accuracy of the individual usage recording. Exclusions: None Business Rules: The accuracy of the data delivery of usage records delivered by BST to the CLEC must enable them to provide a degree of accuracy comparative to BST bills rendered to their retail customers. If errors are detected in the delivery process, they are investigated, evaluated and documented. Errors are corrected and the data retransmitted to the CLEC. Calculations: Usage Data Delivery Accuracy = Σ [(Total number of usage data packs sent during current month) – (Total number of usage data packs requiring retransmission during current month)] / (Total number of usage data packs sent during current month) X 100 Report Structure: CLEC Specific, CLEC Aggregate and BST Aggregate Level of Disaggregation: Geographic Scope Region Data Retained Relating to CLEC Experience: Report Month Record Type BellSouth Recorded Non BellSouth Recorded Non BellSouth Recorded Retail Analog/Benchmark:	acceptable format to the appropriate Competitive	Local Exchange Carrier (CLEC). These percentages
Exclusions: None Business Rules: The accuracy of the data delivery of usage records delivered by BST to the CLEC must enable them to provide a degree of accuracy comparative to BST bills rendered to their retail customers. If errors are detected in the delivery process, they are investigated, evaluated and documented. Errors are corrected and the data retransmitted to the CLEC. Calculations: Usage Data Delivery Accuracy = Σ [(Total number of usage data packs sent during current month) − (Total number of usage data packs requiring retransmission during current month)] / (Total number of usage data packs sent during current month) X 100 Report Structure: CLEC Specific, CLEC Aggregate and BST Aggregate Level of Disaggregation: • Geographic Scope ➤ Region Data Retained Relating to CLEC Experience: • Report Month • Record Type ➤ BellSouth Recorded ➤ Non BellSouth Recorded Retail Analog/Benchmark:	measurement captures Data Delivery Accuracy rat	
None		
Business Rules: The accuracy of the data delivery of usage records delivered by BST to the CLEC must enable them to provide a degree of accuracy comparative to BST bills rendered to their retail customers. If errors are detected in the delivery process, they are investigated, evaluated and documented. Errors are corrected and the data retransmitted to the CLEC. Calculations: Usage Data Delivery Accuracy = Σ [(Total number of usage data packs sent during current month) – (Total number of usage data packs requiring retransmission during current month)] / (Total number of usage data packs sent during current month) X 100 Report Structure: CLEC Specific, CLEC Aggregate and BST Aggregate Level of Disaggregation: • Geographic Scope > Region Data Retained Relating to CLEC Experience: • Report Month • Record Type > BellSouth Recorded > Non BellSouth Recorded Retail Analog/Benchmark:		
The accuracy of the data delivery of usage records delivered by BST to the CLEC must enable them to provide a degree of accuracy comparative to BST bills rendered to their retail customers. If errors are detected in the delivery process, they are investigated, evaluated and documented. Errors are corrected and the data retransmitted to the CLEC. Calculations: Usage Data Delivery Accuracy = Σ [(Total number of usage data packs sent during current month) – (Total number of usage data packs requiring retransmission during current month)] / (Total number of usage data packs sent during current month) X 100 Report Structure: CLEC Specific, CLEC Aggregate and BST Aggregate Level of Disaggregation: • Geographic Scope > Region Data Retained Relating to CLEC Experience: Data Retained Relating to BST Performance: • Report Month • Record Type > BellSouth Recorded > Non BellSouth Recorded Retail Analog/Benchmark:		
provide a degree of accuracy comparative to BST bills rendered to their retail customers. If errors are detected in the delivery process, they are investigated, evaluated and documented. Errors are corrected and the data retransmitted to the CLEC. Calculations: Usage Data Delivery Accuracy = Σ [(Total number of usage data packs sent during current month) – (Total number of usage data packs requiring retransmission during current month)] / (Total number of usage data packs sent during current month) X 100 Report Structure: CLEC Specific, CLEC Aggregate and BST Aggregate Level of Disaggregation: • Geographic Scope > Region Data Retained Relating to CLEC Experience: • Report Month • Record Type > BellSouth Recorded > Non BellSouth Recorded Retail Analog/Benchmark:		
detected in the delivery process, they are investigated, evaluated and documented. Errors are corrected and the data retransmitted to the CLEC. Calculations: Usage Data Delivery Accuracy = Σ [(Total number of usage data packs sent during current month) – (Total number of usage data packs requiring retransmission during current month)] / (Total number of usage data packs sent during current month) X 100 Report Structure: CLEC Specific, CLEC Aggregate and BST Aggregate Level of Disaggregation: • Geographic Scope > Region Data Retained Relating to CLEC Experience: • Report Month • Record Type > BellSouth Recorded > Non BellSouth Recorded Retail Analog/Benchmark:	The accuracy of the data delivery of usage records	delivered by BST to the CLEC must enable them to
and the data retransmitted to the CLEC. Calculations: Usage Data Delivery Accuracy = ∑ [(Total number of usage data packs sent during current month) − (Total number of usage data packs requiring retransmission during current month)] / (Total number of usage data packs sent during current month) X 100 Report Structure: CLEC Specific, CLEC Aggregate and BST Aggregate Level of Disaggregation: • Geographic Scope > Region Data Retained Relating to CLEC Experience: • Report Month • Record Type > BellSouth Recorded > Non BellSouth Recorded Retail Analog/Benchmark:	detected in the delivery process, they are investigated	ted evaluated and documented. Errors are corrected
Calculations: Usage Data Delivery Accuracy = Σ [(Total number of usage data packs sent during current month) – (Total number of usage data packs requiring retransmission during current month)] / (Total number of usage data packs sent during current month) X 100 Report Structure: CLEC Specific, CLEC Aggregate and BST Aggregate Level of Disaggregation: • Geographic Scope ▶ Region Data Retained Relating to BST Performance: • Report Month • Report Month • Record Type ▶ Record Type ▶ BellSouth Recorded ▶ Non BellSouth Recorded ▶ Non BellSouth Recorded Retail Analog/Benchmark:	and the data retransmitted to the CLFC	
Usage Data Delivery Accuracy = Σ [(Total number of usage data packs sent during current month) − (Total number of usage data packs requiring retransmission during current month)] / (Total number of usage data packs sent during current month) X 100 Report Structure: CLEC Specific, CLEC Aggregate and BST Aggregate Level of Disaggregation: • Geographic Scope ➤ Region Data Retained Relating to CLEC Experience: • Report Month • Record Type ➤ BellSouth Recorded ➤ Non BellSouth Recorded Retail Analog/Benchmark:	· · · · · · · · · · · · · · · · · · ·	
Report Structure: CLEC Specific, CLEC Aggregate and BST Aggregate Level of Disaggregation: Geographic Scope Region Data Retained Relating to CLEC Experience: Report Month Record Type BellSouth Recorded Non BellSouth Recorded Retail Analog/Benchmark:	(Total number of usage data packs requiring retran	smission during current month)] / (Total number of
Level of Disaggregation:	Y	
Level of Disaggregation:		
Geographic Scope Region Data Retained Relating to CLEC Experience: Report Month Record Type BellSouth Recorded Non BellSouth Recorded Retail Analog/Benchmark: Geographic Scope Region Data Retained Relating to BST Performance: Report Month Record Type Record Type Record Type		
▶ Region Data Retained Relating to CLEC Experience: Data Retained Relating to BST Performance: • Report Month • Report Month • Record Type • Record Type ▶ BellSouth Recorded Pon BellSouth Recorded Retail Analog/Benchmark: Retail Analog/Benchmark		
 Report Month Record Type BellSouth Recorded Non BellSouth Recorded Retail Analog/Benchmark: Report Month Record Type 		
 Record Type ▶ BellSouth Recorded ▶ Non BellSouth Recorded Retail Analog/Benchmark: 	Data Retained Relating to CLEC Experience:	Data Retained Relating to BST Performance:
 ➢ BellSouth Recorded ➢ Non BellSouth Recorded Retail Analog/Benchmark: 	Report Month	Report Month
> Non BellSouth Recorded Retail Analog/Benchmark:	Record Type	Record Type
Retail Analog/Benchmark:		
	Non BellSouth Recorded	
Retail Analog		
	Retail Analog	

Revision date: 08/0/99 (lg)

BILLING

Report/Measurement:	
Usage Data Delivery Completeness	
Definition:	
by BellSouth and usage recorded by other compar transmitted to the CLEC within thirty (30) days of provided showing completeness of BST messages delivers its own retail usage from recording location billing data to other companies. Timeliness, Compare reported on the same report.	te and accurately recorded usage data (usage recorded lies and sent to BST for billing) that is processed and the message recording date. A parity measure is also processed and transmitted via CMDS. BellSouth on to billing location via CMDS as well as delivering pleteness and Mean Time to Deliver Usage measures
Exclusions:	
None	
Business Rules:	
The purpose of these measurements is to demonstrate the level of quality of usage data delivered to the appropriate CLEC. Method of delivery is at the option of the CLEC.	
Calculation:	
Usage Data Delivery Completeness = Σ (Total number of Recorded usage records delivered during the current month that are within thirty (30) days of the message recording date) / Σ (Total number of Recorded usage records delivered during the current month) X 100	
Report Structure	
CLEC Specific, CLEC Aggregate, BST Aggregate	
Level of Disaggregation:	
Geographic Scope ▶ Region	
Data Retained Relating to CLEC Experience:	Data Retained Relating to BST Performance:
Report Month	Report Monthly
Record Type	Record Type
BellSouth Recorded	
Non BellSouth Recorded	
Retail Analog/Benchmark:	
Retail Analog	

Revision date: 08/02/99 (lg)

BILLING

Report/Measurement:		
Usage Data Delivery Timeliness		
Definition:		
This measurement provides a percentage of recorded usage data (usage recorded by BST and usage		
recorded by other companies and sent to BST for	billing) that is delivered to the appropriate CLEC	
within six (6) calendar days from the receipt of th	ne initial recording. A parity measure is also provided	
	nd transmitted via CMDS. Timeliness, Completeness	
and Mean Time to Deliver Usage measures are re	ported on the same report.	
Exclusions:		
None		
Business Rules:	4-41-111	
The purpose of this measurement is to demonstra	priate CLEC. The usage data will be mechanically	
	g center once daily. The Timeliness interval of usage	
recorded by other companies is measured from the date BST receives the records to the date BST distributes to the CLEC. Method of delivery is at the option of the CLEC.		
Calculation:		
Usage Data Delivery Timeliness = Σ (Total number of usage records sent within six (6) calendar days		
from initial recording/receipt) / Σ (Total number of usage records sent) X 100		
Report Structure:		
CLEC Aggregate		
CLEC Specific		
BST Aggregate		
Level of Disaggregation:		
Geographic Scope		
≽ Region		
Data Retained Relating to CLEC Experience: Data Retained Relating to BST Performance:		
Report Month	Report Monthly	
Record Type	Record Type	
BellSouth Recorded		
Non-BellSouth Recorded		
Retail Analog/Benchmark:		
Retail Analog		

Revision date: 08/02/99 (lg)

BILLING

Report/Measurement:	
Mean Time to Deliver Usage	
Definition:	
measure is also provided showing timeliness of I	akes to deliver Usage Records to a CLEC. A parity BST messages processed and transmitted via CMDS. eliver Usage measures are reported on the same report.
Exclusions:	
None	
Business Rules:	
Usage data to the appropriate CLEC. Usage data data processing center once daily. Method of de	ate the average number of days it takes BST to deliver a is mechanically transmitted or mailed to the CLEC livery is at the option of the CLEC.
Calculation:	
	ne X estimated number of days to deliver the Usage
Record) / total record volume	
Report Structure:	- Annual Control of the Control of t
CLEC Aggregate	
 CLEC Specific 	
BST Aggregate	
Level of Disaggregation:	
 Geographic Scope 	
Region	
Data Retained Relating to CLEC Experience:	Data Retained Relating to BST Performance:
Report Month	Report Monthly
Record Type	Record Type
BellSouth Recorded	
➤ Non-BellSouth Recorded	
Retail Analog/Benchmark:	
Retail Analog	

Revision date: 07/30/99 (lg)

Appendix D2 - SQM Reg 8-10-99

OPERATOR SERVICES AND DIRECTORY ASSISTANCE

Report/Measurement:

Speed to Answer Performance/Average Speed to Answer - Toll

Definition:

Measurement of the average time in seconds calls wait before answered by a toll operator.

Exclusions:

Calls abandoned by customers are not reflected in the average speed to answer but are reflected in the conversion tables where the percent answered within "X" seconds is determined.

Business Rules:

The call waiting measurement scan starts when the customer enters the queue and ends when a BST representative answers the call. The average speed to answer is determined by measuring and accumulating the seconds of wait time from the entry of a customer into the BST call management system queue until the customer is transferred to a BST representative. No distinction is made between CLEC customers and BST customers.

Calculation:

The Average Speed to Answer for toll is calculated by using data from monthly system measurement reports taken from the centralized call routing switches. The "total call waiting seconds" is a subcomponent of this measure which BST systems calculate by monitoring the number of calls in queue throughout the day multiplied by the time (in seconds) between monitoring events. The "total calls served" is the other sub-component of this measure, which BST systems record as the total number of calls handled by Operator Services toll centers. Since calls abandoned are not reflected in the calculation, the percent answered within the required timeframe is determined by using conversion tables with input for the abandonment rate.

Report Structure:

Reported for the aggregate of BST and CLECs

State

Level of Disaggregation:

None

Data Retained (on Aggregate Basis)

For the items below, BST's Performance Measurement Analysis Platform (PMAP) receives a final computation; therefore, no raw data file is available in PMAP.

- Month
- Call Type (Toll)
- Average Speed of Answer

Retail Analog/Benchmark

Parity by Design

Revision Date: 06/29/99 (tg)

OPERATOR SERVICES AND DIRECTORY ASSISTANCE

Report/Measurement:

Speed to Answer Performance/Percent Answered within "X" Seconds - Toll

Definition:

Measurement of the percent of toll calls that are answered in less than "X" seconds. The number of seconds represented by "X" is thirty, except where a different regulatory benchmark has been set against the Average Speed to Answer by a State Commission.

Exclusions:

Calls abandoned by customers are not reflected in the average speed to answer but are reflected in the conversion tables where the percent answered within "X" seconds is determined.

Business Rules:

The call waiting measurement scan starts when the customer enters the queue and ends when a BST representative answers the call. The average speed to answer is determined by measuring and accumulating the seconds of wait time from the entry of a customer into the BST call management system queue until the customer is transferred to a BST representative. No distinction is made between CLEC customers and BST customers.

Calculation:

The Percent Answered within "X" Seconds measurement for toll is derived by using the BellCore Statistical Answer Conversion Tables, to convert the Average Speed to Answer measure into a percent of calls answered within "X" seconds. The BellCore Conversion Tables are specific to the defined parameters of work time, number of operators, max queue size and call abandonment rates.

Report Structure:

Reported for the aggregate of BST and CLECs

State

Level of Disaggregation:

None

Data Retained (on Aggregate Basis)

For the items below, BST's Performance Measurement Analysis Platform (PMAP) receives a final computation; therefore, no raw data file is available in PMAP.

- Month
- Call Type (Toll)
- Average Speed of Answer

Retail Analog/Benchmark

Parity by Design

Revision Date: 06/29/99 (tg)